

MaxFit E Series

Dual Power Supply Expandable Power Systems



Altronix MaxFit Expandable Power Systems provide system designers and installers with optimum power choices and the highest levels of versatility. They provide 12VDC, 24VDC, or 12VDC and 24VDC simultaneously via two (2) single output power supplychargers. Suit of features includes AC fail, low battery, and battery presence monitoring. Enclosure accommodates up to four (4) 12VDC/12AH batteries.



MaxFit35E

Key Features

- Filtered and electronically regulated outputs
- Thermal and short circuit protection with auto reset.
- Supervision
 - AC Fail
 - Low Battery and Battery Presence
- Built-in charger for sealed lead acid or gel type batteries
- Instantaneous transfer to stand-by batteries
- AC input and DC output LED indicators
- Enclosure accommodates up to four (4) 12VDC/12AH batteries
- Lifetime Warranty

MaxFit E Series Dual Power Supply Configuration Reference Chart

Altronix Model Number	Output Voltage Options		Non Power-Limited Outputs	Class 2 Rated Power-Limited Outputs	115VAC 60Hz Input Current	Power Supply Board Input Fuse Rating	Power Supply Board Battery Fuse Rating
	Power Supply 1	Power Supply 2					
MaxFit11E	AL400ULXB2	AL400ULXB2	-	2	7.0A	5A/250V	15A/32V
	12VDC @ 4A	12VDC @ 4A					
	12VDC @ 4A	24VDC @ 3A					
MaxFit13E	AL600ULXB	AL400ULXB2	1	1	7.0A	5A/250V	15A/32V (AL400ULXB2)
	12VDC @ 6A	12VDC @ 4A					
	24VDC @ 6A	12VDC @ 4A					
	12VDC @ 6A	24VDC @ 3A					
MaxFit33E	AL600ULXB	AL600ULXB	2	-	7.0A	5A/250V	-
	12VDC @ 6A	12VDC @ 6A					
	12VDC @ 6A	24VDC @ 6A					
	24VDC @ 6A	24VDC @ 6A					
MaxFit35E	AL1012ULXB	AL600ULXB	2	-	6.1A	5A/250V	15A/32V (AL1012ULXB)
	12VDC @ 10A	12VDC @ 6A					
	12VDC @ 10A	24VDC @ 6A					
MaxFit37E	AL1024ULXB2	AL600ULXB	2	-	7.9A	5A/250V	15A/32V (AL1024ULXB2)
	24VDC @ 10A	12VDC @ 6A					
	24VDC @ 10A	24VDC @ 6A					
MaxFit55E	AL1012ULXB	AL1012ULXB	2	-	5.2A	5A/250V	15A/32V
	12VDC @ 10A	12VDC @ 10A					
MaxFit75E	AL1024ULXB2	AL1012ULXB	2	-	7.0A	5A/250V	15A/32V
	24VDC @ 10A	12VDC @ 10A					
MaxFit77E	AL1024ULXB2	AL1024ULXB2	2	-	8.8A	5A/250V	15A/32V
	24VDC @ 10A	24VDC @ 10A					

MaxFit E Series

Dual Power Supply Expandable Power Systems

Specifications

Input

Voltage	115VAC, 60Hz
Fusing	5A/250V

Outputs

Voltage	12VDC or 24VDC, see Reference Chart
Current	Varies, see Reference Chart
Other	Oversoltage protection Filtered and regulated

Back-up Battery *(not included)*

Capacity	12AH / 12VDC (Up to 4 within enclosure) 40 AH / 65 AH (requires separate enclosure)
Type	Sealed lead acid or gel type
Fuse Rating	15A @ 32VDC AL600ULXB does not have a battery fuse
Failover	Upon AC loss, instantaneous

Supervision

AC Failure	Form "C" contacts
Battery	Form "C" contacts

Indicators (LED)

Input	115VAC is present
DC Output	Powered
Battery	Discharged or not connected

Physical and Environmental

Dimensions (H x W x D)

20.5" x 16.5" x 6.25" (520.7mm x 419.1mm x 158.8mm)

Weight (approx.)

Model	Product Weight	Shipping Weight
MaxFit11E	21.2 lb. (9.6 kg)	26.6 lb. (12.1 kg)
MaxFit13E	21.2 lb. (9.6 kg)	26.6 lb. (12.1 kg)
MaxFit33E	21.2 lb. (9.6 kg)	26.6 lb. (12.1 kg)
MaxFit35E	21.2 lb. (9.6 kg)	26.6 lb. (12.1 kg)
MaxFit37E	21.2 lb. (9.6 kg)	26.6 lb. (12.1 kg)
MaxFit55E	21.2 lb. (9.6 kg)	26.6 lb. (12.1 kg)
MaxFit75E	21.2 lb. (9.6 kg)	26.6 lb. (12.1 kg)
MaxFit77E	21.7 lb. (9.8 kg)	27.1 lb. (12.3 kg)

Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity

85% +/-5%

BTU/Hr (approx.):

Model	12VDC	24VDC	12 and 24VDC
MaxFit11E	43	66	55
MaxFit13E	45	82	45 or 82*
MaxFit33E	74	147	111
MaxFit35E	98	N/A	130
MaxFit37E	N/A	197	160
MaxFit55E	123	N/A	N/A
MaxFit75E	N/A	N/A	184
MaxFit77E	N/A	246	N/A

*Depending on Power Supplies' settings

Lifetime Warranty