

## Panic Device Power Controller



Altronix Strikelt2 operates one (1) 24VDC panic hardware device. It is designed to handle the high current surge panic hardware locking devices demand. In addition, an auxiliary power output provides power for accessory devices such as card readers, keypads, REX PIRs, electronic timers, relays, etc.



Strikelt2

### Specifications

#### Input

Voltage	115VAC, 60Hz, 7A One (1) NO trigger input
Fusing	Input fuse rating: 6.3A

#### Outputs

##### Power options:

- One (1) 23.2-24VDC lock output rated up to 16A for 300ms, 0.5A continuous hold current
- One (1) 23.2-24VDC filtered regulated auxiliary output rated at 0.5A continuous supply current

\*Note: Total combined current for the outputs may not exceed 1A

#### Back-up Battery

Type	Sealed lead acid or gel type
Failover	Upon AC loss, instantaneous
When 4AH batteries are used, battery capacity for emergency stand-by is 30 minutes	

#### Indicators (LED)

AC Power (Green)	Input voltage is present
DC Output (Red)	24VDC is on

#### Agency Listings

UL	UL294 (Access Control System Units)
cUL	CSA Standard C22.2 No.205-M1983, Signal Equipment.
CSFM	California State Fire Marshal Approved

#### Physical and Environmental

##### Dimensions (H x W x D)

8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm).

Enclosure accommodates up to two (2) 12VDC/4AH batteries.

Product Weight 4.85 lb. (2.2 kg)

Shipping Weight 5.45 lb. (2.47 kg)

##### Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

BTU/Hr. (approx.): 14 BTU/Hr.

#### Lifetime Warranty