

Trove1

Versatile Access & Power Integration Enclosure



Altronix Trove1 can house Altronix backplanes which accommodate various combinations of access controllers and accessories from the industry's leading manufacturers with or without Altronix power supplies and accessories for access systems. Trove systems simplify board layout and wire management, reducing installation time and labor costs.



Trove1

Specifications

Features

- 16 AWG powder coated steel.
- Convenient knockout configuration:
 - One (1) double knockout
1.948" (1-1/2" Conduit) / 1.701" (1-1/4" Conduit).
 - Nine (9) double knockouts
1.362" (1" Conduit) / 1.115" (3/4" Conduit).
- Includes cam lock, tamper switch and mounting hardware.

Agency Listings

- UL: UL 294 Access Control Unit Accessory Enclosure.
 cUL: cUL Listed For CSA Standard C22.2 No.205-M1983, Signal Equipment.
 CE European Conformity

Capacity

- Accommodates up to two (2) 12VDC/7AH batteries

Physical and Environmental

Dimensions (H x W x D)

18.0" x 14.5" x 4.625" (457.2mm x 368.3mm x 117.5mm).

Product Weight 11.8 lb. (5.35 kg).

Shipping Weight 15.5 lb. (6.83 kg).

Optional Backplanes

Backplane Model	Backplane with Enclosure Model	Manufacturer	Dimensions (H x W x D)
TC1	TROVE1C1	CDVI	16.625" x 12.5" x 0.3125" (422.3mm x 317.5mm x 8mm)
	TROVE1PH1	Openpath	
TDM1	TROVE1DM1	DMP Wiegand	
THC1	TROVE1HC1	Hartmann	
TM1	TROVE1M1	Mercury	
TPD1	TROVE1PD1	PDK	
TSA1	TROVE1SA1	Salto	
TV1	TROVE1V1	HID Vertx	

Dimensions and Drawing

Dimensions (H x W x D approximate)

18.0" x 14.5" x 4.625" (457.2mm x 368.3mm x 117.5mm)

