

# TroveHR2R

Rack Access and Power Integration Solution for Identiv



Altronix Trove2HR2R consists of a high-capacity rack enclosure with removable backplane. This unit easily combines Altronix power/accessories with various combinations of Identiv boards in a streamlined package. Trove simplifies board layout and wire management, reducing installation time and labor costs.



Trove2HR2R



## Trove2HR2R (Trove2R Enclosure + THR2R Backplane) and THR2R (Backplane) Features

- Accommodates the following Hirsch Identiv controllers with or without Altronix power/accessories:
  - One (1) Mx2, Mx4, and Mx8 with CCMx and SNIB3.
  - Up to four (4) RREB, AEB8 and REB8
  - Altronix Power Supplies, Sub-Assemblies
- Includes Altronix Trove2R Rack Enclosure & one (1) removable THR2R backplane

### Agency Listings

CE European Conformity

### Features

- Power status LED for use where power and access control boards share the same enclosure
- Simplifies board layout and wire management
- Convenient knockout configuration:
  - Four (4) double knockouts - 3/4" Conduit and 1" Conduit
  - Two (2) double knockouts - 1/2" Conduit and 3/4" Conduit
- 2U drawer on extendable rails
- Included Z Bracket facilitates ease of wiring
- Black powder coated steel enclosure
- Includes cam lock, tamper switch, IEC320 connector and mounting hardware

### Physical and Environmental:

#### Trove2HR2R

##### Dimensions (H x W x D):

Modular 2U standard EIA 19" rack mount chassis

Enclosure:

3.375" x 19.0" x 33.25" (85.8mm x 482.6mm x 844.6mm).

Shipping:

7.75" x 22.5" x 42.0" (196.9mm x 571.5mm x 1,066.8mm)

##### Weights (approx.):

Product: 30.0 lb. (13.61 kg)

Shipping: 35.5 lb. (16.10 kg)

#### THR2R

##### Dimensions (H x W x D):

Backplane:

32.0" x 14.375" x 0.375" (812.8mm x 365.1mm x 9.5mm)

Shipping:

36.0" x 30.0" x 1.25" (915mm x 762mm x 32mm)

##### Weight (approx.)

Product: 4.5 lb. (2.04 kg)

Shipping: 9.3 lb. (4.22 kg)

## Accessories (order separately)



WM5

### WM5, WM25, WM100 - Magnetic Cable Tie Mounts

Altronix WM5, WM25, and WM100 are packs of 5, 25 or 100 magnetic cable tie mounts respectively.

They accommodate standard zip ties or velcro straps. These are ideal for wire management in our Trove series.



RE2

### RE2 - Rack Mount Battery Enclosure

RE2 accommodates up to four (4) 12VDC/7AH batteries.




LC3

### LC3 - Line Cord

18 AWG gauge 6 ft. three-wire line cord with IEC Connector

### Access Controller Position Chart for the Following Models:

Altronix / Identiv	Pem Mounting
eFlow104NB connects to Altronix sub-assemblies in positions C, D, and E	(A)
AL1024ULXB2 (set for 28VDC) connects to Mx8 board (position G)	(B)
ACMS8(CB), LINQ8ACM(CB)	(C)
LINQ8PD(CB), PDS8(CB), VR6	(D)
LINQ8PD(CB), PDS8(CB), VR6	(E)
RREB, AEB8 and REB8	(F)
Mx2, Mx4, and Mx8 with CCMx and SNIB3	(G)



# Trove2HR2R

Rack Access and Power Integration Solution for Identiv



## Dimensions and Drawing

Dimensions (H x W x D approximate)

3.375" x 19.0" x 33.25" (85.8mm x 482.6mm x 844.6mm). Shown with Z Bracket attached.

