

## VertiLineD Series

Eight (8) Output CCTV DC Rack Mount Power Supplies

Altronix VertiLine Rack Mount Power Supplies provide eight (8) filtered and electronically regulated power outputs in a space saving 1U EIA 19" rack mount chassis. The units are available with either 12VDC or 24VDC power outputs.

**VERTILINE™**


VertiLine3D

### Key Features

- 115VAC input
- Eight (8) PTC protected outputs
- 12VDC (VertiLine3D) or 24VDC (VertiLine6D) PTC outputs
- Surge protection
- Individual power LED indicators
- Illuminated power disconnect circuit breaker with manual reset
- Removable terminal blocks with locking screw flanges
- CE European Conformity
- Lifetime Warranty

### VertiLineD Series Configuration Reference Chart

Altronix Model Number	115VAC 60Hz Input Current	Output Voltage (VDC)	Total Output Current (Power)	Number of Outputs	Current (max. per output)	Output PTC Rating
VertiLine3D	1.5A	12VDC	8A	8	2.5A	2.5A
VertiLine6D	3A	24VDC	8A	8	2.5A	2.5A

### Specifications

#### Input

Voltage 115VAC, 60Hz

#### Output

Eight (8) PTC protected power outputs. 8A total current max.

#### Voltage

**VertiLine3D:** 12VDC

**VertiLine6D:** 24VDC

#### Other

Short circuit and thermal overload protection  
Filtered and regulated

#### Indicators (LED)

Master Illuminated master power disconnect circuit breaker with manual reset

Output Eight (8) individual LEDs

#### Agency Listings

CE European Conformity

#### Physical and Environmental

##### Dimensions (H x W x D)

Modular 1U standard EIA 19" rack mount chassis  
1.625" x 19.125" x 8.5" (41.3mm x 486mm x 216mm)

##### Weight (approx.)

Model	Product Weight	Shipping Weight
VertiLine3D	6.95 lb. (3.15 kg)	8.05 lb. (3.65 kg)
VertiLine6D	8.0 lb. (3.63 kg)	9.3 lb. (4.22 kg)

##### Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

##### BTU/Hr. (approx.):

**VertiLine3D:** 49 BTU/Hr.

**VertiLine6D:** 98 BTU/Hr.

#### Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com