

eBridge100TM

IP and PoE/PoE+ over Coax Hardened Transceiver



Altronix eBridge100TM EoC hardened transceiver transmits data at 100Mbps, Full Duplex over Coax cable to a paired eBridge receiver and provides power in a PoE/PoE+ compliant format to an enabled device/camera. The eBridge receiver is available in various options and is powered by an external midspan or endspan. The receiver passes PoE/PoE+ power over the same coax cable to the eBridge100TM transceiver, which, in turn, passes this power to an enabled IP camera/device. These plug and play units facilitate a cost-effective, simple way to replace legacy analog products with new IP devices over existing coax up to 300m. When paired with the eBridge100RM EoC Receiver, the eBridge100TM will pass 100Mbps full duplex data and PoE/PoE+ over CAT5e (or higher) up to 500m.



eBridge100TM

Key Features

- IEEE 802.3af (15W) and IEEE 802.3at (30W)
- Passes 100Mbps up to 300m via Coax or 500m via CAT5e
- Eliminates the costs and labor associated with installing new network cabling
- Retrofit digital IP cameras in an analog CCTV installation
- Auto detection and protection of legacy non-PoE cameras/devices
- Works with Megapixel, HD720, HD1080 & VGA (SD) cameras
- Extends Network link distance in an industrial environment
- Upgrades deployed CCTV Coax to a digital network for Retail, Casinos, Airports, Schools, Hospitals, etc.
- UL Listed in the U.S. and Canada
- CE European Conformity
- C-Tick compliant
- Lifetime Warranty

Compatible Receivers:



eBridge100RM -

IP and PoE/PoE+ over Coax or Extended Ethernet Cable Receiver

Transmits data at 100Mbps full duplex and power over Coax cable or extended CAT5e cable in a PoE+ compliant format. Supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at). UL/cUL Listed (UL60950-1). CE and C-Tick Approved.

eBridgePlus Receivers -

eBridge400PCRM - Four (4) Port EoC Receiver

eBridge800PCRM - Eight (8) Port EoC Receiver

eBridge1600PCRM - Sixteen (16) Port EoC Receiver

Transmit IP video/data over coax up to 300m @ 100Mbps.

Supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at).

UL/cUL Listed (UL60950-1). CE and C-Tick Approved.



eBridge800E - Eight (8) Port EoC Receiver with Integral PoE+ Switch

Provides 30W full power per port (240W max) over coax up to 300m @ 100Mbps.

Supports PoE (IEEE 802.3af) or PoE+ (IEEE 802.3at).

UL/cUL Listed (UL60950-1). European Conformity.



Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA

phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com



eBridge100™

IP and PoE/PoE+ over Coax Hardened Transceiver



Specifications

Input

Operating power provided by eBridge receiver
Power draw: 1.5W

Coax

Throughput rated at 100Mbps at distances up to 300m.
Speed: 10/100BaseT, half/full duplex, auto negotiation
Connectivity: BNC, RG-59/U or similar

Ethernet

Throughput rated at 100Mbps at distances up to 500m
Speed: 10/100BaseT, half/full duplex, auto negotiation
Connectivity: RJ45, auto crossover

Indicators (LED)

Yellow and Green LED (by RJ45 jack):
IP Link status, 10/100Base-T/active
Green LED: PoE ON

Agency Listings

UL/cUL	UL 60950-1 (Information Technology Equipment)
CE	European Conformity
C-Tick compliant	

Physical and Environmental

Dimensions (W x L x H)
4.375" x 3.5" x 1" (111.1mm x 88.9mm x 25.4mm)

Weight (approx.)

Product Weight	0.22 lbs. (0.1 kg)
Shipping Weight	0.4 lbs. (0.18 kg)

Temperature

Operating	
For 15W:	-40°C to 75°C (-40°F to 167°F)
For 25W:	-40°C to 60°C (-40°F to 140°F)
For 30W:	-40°C to 49°C (-40°F to 120.2°F)

Storage	-40°C to 75°C (-40° to 167°F)
---------	-------------------------------

Relative Humidity	85% +/-5%
-------------------	-----------

Operating Altitude:	-304.8 to 2,000m
---------------------	------------------

Lifetime Warranty

Altronix Corporation | 140 58th St | Brooklyn, NY 11220 USA
phone: +1 718.567.8181 | fax: +1 718.567.9056 | email: info@altronix.com | www.altronix.com